

Acryl 80

ACRYL 80 is a water based acryl paint for interior, featuring both good resistant of applied film and good vapour diffusion rate.

ACRYL 80 is suitable for any interior wall where it is required a good quality paint at reasonable price. Good hiding power and coverage, easy to apply, **ACRYL 80** protects the wall against moulds, thanks to a lemon scented fungicide.

COLOURS: White and tintosystem colours

SURFACE

PREPARATION: New walls: apply one coat of SAIFSEAL ACRYL 300% (dilution by

water: 300%).

Old walls: brush all flaking and dusty old paints, clean carefully and apply one coat of **SAIFSEAL DUR** (dilution 300% by water). On deteriorated dusty plasters: apply one coat of **SAIFSEAL DUR**

300%.

Old mouldy walls: first apply one or two coats of "**NO MOULD**". After drying, take out all dusty staff and proceed with one coat

of SAIFSEAL SAN (mould inhibitor undercoat).

APPLICATION: According to surface absorption, dilute from 20 to 30% by water.

Mix the product throughly before application. Apply two coats by brush, power or airless spray-gun. Second coat dilution: 20%. Do not apply under + 5° C.. **ACRYL 80** is odourless, any way,

keep windows open while the coat is drying.



Acryl 80

>ACRYL 80		N A 02
ACKIL 60		REV 0
		05/11/2004
		SPEC. REF. A 02
TECHNICAL DATA		
Binding agent :	Modified acryl resin	
Specific weight:	1,63 kg /l ± 2%	UNI 8910
pH:	8,5÷9,5	UNI 8311
Viscosity Brookfield:	50000 CPS a 20° C. S. 5 RPM 5 ± 10%	UNI 8490
% Solid weight:	66,8% ± 2	ISTR 0007
APPLICATION DATA		
Storage Temperature:	From +5°C to +45°C	
Application Temperature:	From +5°C to +40°C	
Shelf life:	fe: Dry and fresh store, packed and sealed 18 months	
	least.	
Dilution:	20-30% water, according to substrate absorption.	
Drying Time:	1 hours touch dry. Recoatable after 4-6 hours.	
Consumption:	4 - 5 mg/ It	
Packing:	2,5 lt − 5 ℓ − 10 lt − 15 lt.	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.

AZIENDA CON SISTEMA DI GESTIONE QUALITÀ UNI EN ISO 9001:2000 CERTIFICATO DA CERTIQUALITY **SAIF s.r.l.**VIA ACQUI, 31
15014 CANTALUPO – ALESSANDRIA - ITALY
Tel. (0131) 269207 –269208
Fax (0131) 269200

e-mail: <u>saif@saifspa.it</u> <u>www.saifspa.it</u>