



Milleluci

MILLELUCI is a multicoloured coat mixed system for interior surfaces. Highly decorative, based on very resistant binding agents, this traditional coating can be successfully used in heavy duty public places, and everywhere is required a touch of refinement and elegance. **MILLELUCI** is very washable, and resistant to abrasion and scratches.

COLOURS: 47 standard colours.

SURFACE PREPARATION: **Plastered walls:** make sure that the wall is smooth and clean, remove defects, if any, with sandpaper. In case of plastered walls we suggest you to apply previously a coat of **SAIF SEAL DUR 300%** (consolidator for plaster), in order to have a uniform absorption of the product.
Painted walls: make sure of the good quality of the surface, in case of crumbling walls brush and clean them with care. After, fix with a coat of **SAIF SEAL DUR 300%**.

APPLICATION: First apply, by a short fur roller, one or two coats of **UNOCOAT**, **UNO TOP** or **ACRYL 100**, dilution 20-25%. Take care of obtaining a uniform coat.
Get ready to spray the finish coat, carefully protecting the adjacent areas. **MILLELUCI** is ready to use product, but adding 5% (max 10%) water will help to reach best results. Stir slowly by a flat spatula, apply one coat with proper spray machine: pressure 2-2,5 ATM, nozzle 2.5 mm, reservoir under pressure. A further coat as "Touch up", wet on wet will help to uniform the surface.
During application, keep windows and doors opened.
Do not apply when the temperature is below +5°C.
Clean tools by white spirit, immediately after use.



Milleluci

Multicolori

>MILLELUCI		N M 18
		REV 0
		05/11/2004
		SPEC. REF. M 18
TECHNICAL DATA		
Binding Agent:	"Plyolite GOOD YEAR" resin	
Specific weight:	1,03 \pm 2% Kg/l	UNI 8910
pH:		UNI 8311
Viscosity Brookfield:	7000 \div 10000 CPS a 20° C. S. 5 RPM 5 \pm 10%	UNI 8490
% Solid Weight:	28,5% \pm 2	ISTR 0007
APPLICATION DATA		
Storage temperature	From +10°C to +30°C	
Application Temperature:	From +10°C to +40°C	
Shelf life:	dry and fresh store, packed and sealed 9 months minimum	
Dilution:	5 - 10 % water	
Drying Time:	4 hours touch dry.	
Consumption:	0,35 lt/sqm	
Packing:	5 l - 15 l	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.