



Opalite green

OPALITE GREEN is a white matt primer for wood based on water based resins. **OPALITE GREEN** makes uniform and levels the absorption of internal and external wooden surfaces or plastered walls. **OPALITE GREEN** grants easy applicability, good sandability and excellent filling power.

COLOURS: off white matt

SURFACE

APPLICATION: **unpainted and sanded wood:** previously clean the surface removing any loose part or wood dust.

Painted wood: check the adhesion of old paint, remove all loose particles, sand carefully all the surface after correction of small imperfections with putty for wood.

APPLICATION: Apply one or two coats of **OPALITE GREEN**, properly diluted, sanding and cleaning between coats; always wait 8 hours, sand and clean the surface before application of next coat.

APPLICATION TOOLS

brush, roller, spray gun.

FOR EXTERIOR: it is suggested **OPALITE GREEN DUR**, not easy to sand, but more resistant to external conditions and having better adhesion to wood support. Both **OPALITE GREEN** can be painted by **GREEN COAT**.



Opalite green

Fondi green

> OPALITE GREEN		N O 04
		REV 0
		DEL 02/10/2006
		SPEC. REF. O 04
TECHNICAL DATA		
Binding Agent:	Acrylic emulsion modified	
Specific weight:	1,48 kg /l \pm 2%	UNI 8910
pH:	8,5÷9,5	UNI 8311
Viscosity Brookfield:	4000 CPS a 20° C. S. 5 RPM $5 \pm 10\%$	UNI 8490
% Solid by weight:	63% \pm 2	ISTR 0007
APPLICATION DATA		
Storage temperature	From +10°C to +30°C	
Application Temperature:	From +12°C to +40°C	
Shelf life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	5 – 10% with water	
Drying Time:	1 hours touch dry. Recoatable after 72 hours	
Consumption:	from 6 to 8 mq/l each coat	
Packing:	0,500 l - 2,5 l - 15 l	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.