



Oriente

Finishing decorative coat, structured by micro glass bead filler.

ORIENTE dress the wall by a bright and refined effect, creating full of light and colours leaving areas scenographic effects can be reached in halls, entrances and areas where sophisticated atmosphere are required.

COLOURS: 28 standard colours available by toners or tintosystem.
Gold, silver and red bases are available.

SURFACE PREPARATION: Smooth surfaces, dry walls need to be primed by one coat of **SAIFSEAL DUR 300%** and two coat of **MICROFINE 500** or **ACRYL 100** white.

APPLICATION: **ORIENTE** is ready to use. Apply 1° coat by flat brush, crossing each stroke, spreading uniformly the product. 2° coat: apply the same way as first coat. Alternatively, on wet applied second coat, a fine large sponge or a haired glove can be passed to get a softer and shaded effect. If small areas show concentration of "sand", this is not a defect.
Clean tools immediately after use, by warm water and soap.



Oriente

Stucchi perlescenti

>ORIENTE		N O 05
		REV 0
		DEL 02/04/2009
		SPEC. REF. O 05
TECHNICAL DATA		
Binding Agent:	Acryl resin	
Specific weight:	1,11 kg /l \pm 2%	UNI 8910
pH:	8,5÷9,5	UNI 8311
Viscosity Brookfield:	12000 CPS a 20° C. S. 5 RPM $5 \pm 10\%$	UNI 8490
% Solid by weight:	40,5% \pm 2	ISTR 0007
APPLICATION DATA		
Storage temperature	From +10°C to +35°C	
Application Temperature:	From +10°C to +30°C	
Shelf life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	Ready to use	
Drying Time:	2 hours touch dry. Recoatable after 8 hours	
Consumption:	0,15 l/mq for coat	
Packing:	0,750 l - 2,5 l	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.