



## Pratica V.O.C. $\cong 0$

**PRATICA NEW V.O.C.  $\cong 0$**  is a water based acryl paint suitable for any interior wall where it is required a high vapour permeability (kitchens, bathrooms, ceilings etc.) and industrial areas, where good performances are required, joined to a reasonable price. Good hiding power and coverage, easy to apply, **PRATICA NEW V.O.C.  $\cong 0$**  protects the wall against moulds, thanks to a lemon scented non volatile fungicide.

**PRATICA NEW V.O.C.  $\cong 0$**  is an environmental friendly very low V.O.C. paint, in accordance with European Rules related to organic compounds emissions (Directive C.E. 2004/42 and DL 161 27-03-06)

**COLOURS:** White – matt, light colours available by tinting system.

**SURFACE PREPARATION:** **New surfaces:** apply one coat of **SAIFSEAL BETON 300%** diluted 300% water.  
**Old surfaces:** insure that all surfaces are dry, uniform and clean. Repair all defects, if any, prior to any application and then apply **SAIFSEAL DUR consolidante**, diluted 300% with water. In case the wall surface is weak and powdery, apply **SAIFSEAL DUR consolidante**. In case any presence of mould or other type of fungus growth, apply **NO MOULD** by brush or roller. When the surface is completely dry in approximately three to four hours, remove the remaining mould with a dry cotton rag.

**APPLICATION:** Dilute **PRATICA NEW V.O.C.  $\cong 0$**  with 20-30% water. The dilution percentage is based on the porosity and absorption of paint in the wall.  
Blend thoroughly by using a flat tool.  
Apply two coats of **PRATICA NEW V.O.C.  $\cong 0$**  by brush, roller or spray gun. Two coats are suggested at four to six hour intervals..  
Do not apply when the temperature is below +5 degrees centigrade.  
**PRATICA NEW V.O.C.  $\cong 0$**  is non-toxic and contains no solvents. Therefore cleaning may be done by simply washing with water and or a mild detergent.



Pratica V.O.C.  $\cong 0$

<b>&gt;PRATICA V.O.C. <math>\cong 0</math></b>		N P 14
		REV 0
		22/03/2008
		SPEC. REF. P 11
<b>TECHNICAL DATA</b>		
Binding agent :	Styro-Acrl Resin.	
Specific weight:	1,67 kg /l $\pm 2\%$	UNI 8910
pH:	8,5÷9,5	UNI 8311
Viscosity Brookfield:	40000 CPS a 20° C. S. 5 RPM 5 $\pm 10\%$	UNI 8490
% Solid weight:	% $\pm 2$	ISTR 0007
<b>APPLICATION DATA</b>		
Storage Temperature:	from +5°C to +40°C	
Application Temperature:	from da +10°C to +40°C	
Shelf life:	store in non-freezing and dry spaces. If stored in sealed drums, the materials can be stored for at least 18 months.	
Dilution:	20-30% of water depending on the absorption of wall surfaces.	
Drying Time:	One hour to be touch dry. Repainting may be performed within four to six hours.	
Consumption:	4 mq/lt	
Packing:	14 l	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.