



Saifseal Dur 300%

SAIFSEAL DUR 300% is a transparent water based sealer suitable for gypsum boards, plasters, deteriorated plasters, old walls already painted. The binding agent micro molecules penetrate the surface achieving three effects:

1. Consolidate the surface
2. Uniform the absorption
3. Improve the adhesion of the next paint to be applied

COLOUR: Milky, transparent when dry

APPLICATION: **SAIFSEAL DUR** can be applied on dry gypsum board -fibre cement - plaster. etc... First, if necessary, take out all loosing stuff, by iron brushing the surface. Apply one coat of **SAIFSEAL DUR** dilution 300%.

Highly absorbent surfaces may require 300% dilution and two coats. Allow few hours between applications. Before each application, mix well the product. Apply by roller or brush.



Saifseal Dur 300%

>SAIFSEAL DUR 300%		N S 03
		REV 0
		05/11/2004
		SPEC. REF. S 03
TECHNICAL DATA		
Binding Agent:	Modified Acrylic Resin	
Specific weight:	1,04 Kg/l \pm 2%	UNI 8910
pH:	8,5 \div 9,5	UNI 8311
Viscosity Brookfield:	10 \div 20 CPS to 20° C. S. 1 RPM 10 \pm 10%	UNI 8490
% Solid weight:	19,3% \pm 2	ISTR 0007
APPLICATION DATA		
Shelf Life Temperature:	From +5°C to +40°C	
Application Temperature:	From +5°C to +45°C	
Shelf Life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	300% by water.	
Drying Time:	2 hour touch dry. 10 hours to re-coat	
Consumption:	from 0,1 to 0,15 l/mq according to substrate absorption and dilution.	
Packing:	1 l - 5 l - 10 l	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.