



Xilowax

XILOWAX is a protective, penetrating solvent based specific treatment for our interior - exterior "**PIETRA ANTICA**". The combination of wax and silane resins grant, from one side a high and immediate protection against atmospheric agents, from the other side a durable, deep water repellency together with a good vapour permeability rate. These features allow the lime based "**PIETRA ANTICA**" coat to cure properly, avoiding anesthetic whitening stains on the surface.

XILOWAX can also be successfully applied on **MANTOVANO - SENESE - POMPEIANO**, to improve water and dust repellency and making easy the maintenance and cleaning of the surface.

XILOWAX doesn't change the colour of the coating, but enhance the deepness colour effect.

COLOUR: transparent

APPLICATION: apply by pad directly on the surface to be protected. Distribute uniformly allowing good and full penetration of the liquid. After a while, by dry pad, pass on the surface until reaching the required shine effect.



Xilowax

>XILOWAX		N X 06
		REV 0
		05/11/2004
		SPEC. REF. X 06
TECHNICAL DATA		
Binding agent :	silossanic modified	
Specific weight:	0,8kg /l \pm 2%	UNI 8910
pH:		UNI 8311
Viscosity Brookfield:	500÷1000 CPS a 20° C. S. 1 RPM 1 \pm 10%	UNI 8490
% Solid weight:	19,5 \pm 2	ISTR 0007
APPLICATION DATA		
Storage Temperature:	From +10°C to +35°C	
Application Temperature:	From +0°C to +45°C	
Shelf life:	Dry and fresh store, packed and sealed 18 months at least.	
Dilution:	Ready to use .	
Drying Time:	2 hours touch dry.	
Consumption:	From 6 to 8 mq/l depending from the substrate absorption.	
Packing:	1 l - 5 l - 10 l	

These data are result of scrupulous tests and are showing our most updated knowledge. These data are distributed as information and cannot be proof for a dispute since the application and conservation of the product may change not under our responsibility.