According to Decree 7 september 2002

			Page	1 of 4
N.	S 23			
REV.	. 0			
DEL	02/05/	2006		
RIF.	SPEC.	S 23	REV.	0

PRODUCT: SAIFSEAL BETON 300%

Compilation Date: may 2006

## 1. PRODUCT AND COMPANY IDENTIFICATION

## 1.1) PRODUCT'S IDENTIFICATION

Commercial Name: SAIFSEAL BETON 300%

Use: undercoat

## 1.2) COMPANY IDENTIFICATION

Firm: SAIF S.p.a.

Address: Via Acqui n. 31 - 15014 - ALESSANDRIA (ITALIA)

Telephone: 0131 - 269207 / 8

Emergency Telephone: 0131 - 269207 / 8

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

#### CHEMICAL COMPOSITION:

Water Dispersion of Acrylic and Vinylic polymers.

The individual concentration of the substances classified corrosive or harmful or irritant or dangerous for the environment are lower than the limits imposed by Directive 1999/45/CE about the determination of dangerous properties of the product.

### 3. HAZARD IDENTIFICATION

- Eyes and skin contact: The direct contact with eyes or skin may cause irritation
- Inhalation: Inhalation of vapours may cause nausea

According to Decree 7 september 2002

			Page	2 of 4		
N.	S 23		-			
REV	REV. 0					
DEL 02/05/2006						
RIF.	SPEC.	S 23	REV.	0		

PRODUCT: SAIFSEAL BETON 300%

Compilation Date: may 2006

### 4. FIRST AID INTERVENTION

- SKIN CONTACT: Take all contamined clothes off

Wash interested parts with soap and water

- EYES CONTACT: Rinse immediately with plenty of water for 15 minutes...

- INGESTION: If swallowed wash mouth with water. Seek medical advice Never

give anything by mouth to an unconscious person.

- INHALATION: Transfer the patient to a ventilated area.

### 5. FIRE SAFETY MEASURES

The product isn't classified inflammable. Dried product may burn.

- FIRE FIGHTING EQUIPMENT:

Use extinguishing materials appropriate for the surrounding fire

- WRONG EXTINTION'S WAY:

There aren't. Anything could be used.

- RISK FROM EXPOSITION :

Fumes of combustion: Toxic gases (CO, NO, HCI) may also develop thermal decomposition.

- PERSONAL PROTECTION: :

Wear self container breathing apparatus and full protective gear.

#### 6. ACCIDENTAL RELEASE MEAUSURES

- Avoid contact with eyes and skin.
- Avoid the dispersion on sewers and open water.

- CLEANING/ STORING METHODS: Adsorb with inactive materials.

Pick it with appropriate equipment and pour in plastic container

with hermetic lock.

Dispose contaminated material according to law in force

According to Decree 7 september 2002

		Page	e 3 of 4
N. S 23			
REV. 0			
DEL 02/05	/2006		
RIF. SPEC.	S 23	REV.	0

PRODUCT: SAIFSEAL BETON 300%

Compilation Date: may 2006

#### 7. HANDLING AND STORING

- HANDLING

Work according to good pratices and observe safe measures generally valid for chemical product.

- INDICATION AGAINS FIRE AND EXPLOSION:

See section n. 8

- STORING CONDITION

Keep in aerated spaces. Keep from freezing and out of range temperature (See data sheet)

- STORING STABILITY

The product is stable in normal condition. Temperature may slightly vary the viscosity

### 8. PERSONAL PROTECTION / EXPOSURE CONTROL

- EYES PROTECTION:

Wear suitable glasses to avoid squirts in the eyes

- HANDS PROTECTION:

Wear protecting gloves.

- RESPIRATORY PROTECTION:

Any particular respiratory equipment isn't necessary for the normal use of the product.

- EXPOSURE CONTROL

There aren't substances with limit of exposition.

### 9. CHEMICAL AND PHISICAL DATA:

- Physical Form

: gelatinous

- Smell

: not significant

- pH

: 8,5÷9,5

- Flammability

: not flammable

- Comburent power

: not comburent

- Specific weight

: **1,02** ± 2% Kg/l

- Viscosity

: **20.000** ± 10% cps

#### 10. REACTIVITY AND STABILITY

The product is stable under normal temperature condition. It doesn't give dangerous exotermic reactions.

According to Decree 7 september 2002

		Page 4 of 4		
N. S 23				
REV. 0				
DEL 02/05/2006				
RIF. SPEC.	S 23	REV. 0		

PRODUCT: SAIFSEAL BETON QUARTZ

Compilation Date: may 2006

# 11. TOXICOLOGICAL INFORMATIONS

It refers informations about the ingredients of the product..

WATERY DISPERSION OF A VINILIC POLYMER:

LD50 (oral) > 5000 mg/Kg

WATERY DISPERSION OF AN ACRILIC POLYMER:

LD50 (oral) > 5000 mg/Kg

Skin irritation (Rabbit): Practically not irritating Eye irritation (Rabbit): Inconsequential irritation

#### 12. ECOLOGICAL INDICATION

There aren't substances classified dangerous for aquatic and terrestrial environment and for the ozone layer.

### 13. DISPOSAL CONSIDERATIONS

Respect national laws.

The product may be burnt in authorized plants.

### 14. TRANSPORT INFORMATIONS

The products isn't classified dangerous according to transportation laws.

#### 15. REGULATORY INFORMATIONS

The products isn't classified dangerous according to directive 1999/45/CE of 31st may 1999

# 16. OTHER INFORMATIONS

The data reported are based on our actual knowledge, don't represent any guaranty of the characteristics of the product and don't justify any legal contractual relation.